COLD-FORMED METAL FRAMING INSPECTION REPORT SUMMARY

Section 05400

Ins	n	Δ	C	t	<u></u>	r	•
1113	ץי	C	v	·	v	•	•

Name:		D	ate:
Company:			
Address:			
City:	State:	Zi	p code:
Phone:	Fax:	E	mail:
Project:			
Project Name:			
Location:			
Contractor:			
Phone:	Fax:	W	eb Site:
Exterior Non-Axial Load Bearing	ng Wall Sec	tion:	
		(Architectural R	eierence)
Stud Section and Thickness		□ - As Designed	□ - Not Acceptable
2. Vertical Deflection @ Structure		□ - As Designed	□ - Not Acceptable
3. Vertical Deflection & Drift @ Stru	ucture	□ - As Designed	□ - Not Acceptable
4. Stud Bridging		□ - As Designed	□ - Not Acceptable
5. Stud Attachment Bottom Track		□ - As Designed	□ - Not Acceptable
6. Window / Door Openings		□ - As Designed	□ - Not Acceptable
7. Header & Sill Attachment to Jam	nb	□ - As Designed	□ - Not Acceptable
8. Jamb Attachment @ Bottom Tra	ck	□ - As Designed	□ - Not Acceptable
0 Knee Brace		□ - As Designed	□ - Not Accentable

Int	terior Non-Axial Load Bearing Wall Sec	(Architectural Reference)	
1.	Stud Section and Thickness	□ - As Designed	□ - Not Acceptable
2.	Vertical Deflection @ Structure	□ - As Designed	□ - Not Acceptable
3.	Vertical Deflection & Drift @ Structure	□ - As Designed	□ - Not Acceptable
4.	Stud Bridging	□ - As Designed	□ - Not Acceptable
5.	Stud Attachment Bottom Track	□ - As Designed	□ - Not Acceptable
6.	Openings	□ - As Designed	□ - Not Acceptable
7.	Header & Sill Attachment to Jamb	□ - As Designed	□ - Not Acceptable
8.	Jamb Attachment @ Bottom Track	□ - As Designed	□ - Not Acceptable
Ax	kial Load Bearing Wall Section: (Architect	ural Reference)	
1.	Stud Section and Thickness	□ - As Designed	□ - Not Acceptable
2.	Stud Bridging	□ - As Designed	□ - Not Acceptable
3.	Stud Attachment Top & Bottom Track	□ - As Designed	□ - Not Acceptable
4.	Window & Door Openings	□ - As Designed	□ - Not Acceptable
5.	Header & Sill Attachment to Jamb	□ - As Designed	□ - Not Acceptable
6.	Jamb Attachment @ Bottom Track	□ - As Designed	□ - Not Acceptable
7.	Jamb Column & Column Attachment	☐ - As Designed	□ - Not Acceptable
8.	Column Attachment @ Top & Bottom	□ - As Designed	□ - Not Acceptable
9.	Wall Ties	□ - As Designed	□ - Not Acceptable
10	. Knee Brace	□ - As Designed	□ - Not Acceptable
Sh	near Wall Section:(Architectural Reference)		
11	. Infill Stud Section and Thickness	□ - As Designed	□ - Not Acceptable
12	. Stud Bridging	□ - As Designed	□ - Not Acceptable
13	. Stud Attachment Top & Bottom Track	□ - As Designed	□ - Not Acceptable
14	. StiffWall [®] Column & Connection @ Ends	□ - As Designed	□ - Not Acceptable
15	. StiffWall [®] Strap Track	□ - As Designed	□ - Not Acceptable
16	. StiffWall® Flat Strap & Connection @ Ends	□ - As Designed	□ - Not Acceptable
17	. StiffWall [®] Boot	□ - As Designed	□ - Not Acceptable
18	. Anchor Attachment to Deck Above	□ - As Designed	□ - Not Acceptable
19	. Anchor Attachment to Deck Below	□ - As Designed	□ - Not Acceptable
20	. Through Floor Attachment	□ - As Designed	□ - Not Acceptable

Floor Joist Plan:(Architectural Reference)		
Joist Section and Thickness	□ - As Designed	☐ - Not Acceptable
Joist Bearing Length	□ - As Designed	□ - Not Acceptable
Joist Bridging	□ - As Designed	□ - Not Acceptable
		· ·
	□ - As Designed	□ - Not Acceptable
5. Openings	□ - As Designed	□ - Not Acceptable
6. Stair Header Attachment to Built-up Joist	□ - As Designed	□ - Not Acceptable
7. Built-up Girder	☐ - As Designed	□ - Not Acceptable
8. Joist Plates	□ - As Designed	□ - Not Acceptable
Ceiling Joist Plan:		
(Architectural Reference)		
Joist Section and Thickness	□ - As Designed	□ - Not Acceptable
2. Joist Bridging	□ - As Designed	□ - Not Acceptable
3. Joist Attachment @ Ends	□ - As Designed	□ - Not Acceptable
4. Openings	□ - As Designed	□ - Not Acceptable
5. Stair Header Attachment to Built-up Joist	□ - As Designed	□ - Not Acceptable
6. Built-up Girder	□ - As Designed	□ - Not Acceptable
7. Joist Plates	□ - As Designed	□ - Not Acceptable
Roof Rafter Plan:		
(Architectural Reference)	□ As Designed	□ Not Appentable
Rafter Section and Thickness Refter Bridging	□ - As Designed	☐ - Not Acceptable
2. Rafter Bridging	□ - As Designed	□ - Not Acceptable
3. Rafter Attachment @ Ends	□ - As Designed	□ - Not Acceptable
4. Openings (skylight)	☐ - As Designed	□ - Not Acceptable
Header Attachment to Built-up Rafter	□ - As Designed	□ - Not Acceptable
6. Built-up Girder	□ - As Designed	□ - Not Acceptable
Notes:		
-		
Signature		

Exterior Non Axial Load	Doaring Wan Goodon	(Architectural Reference)	
Condition:	Design Requirement	Drawing Reference	Inspected As-Built
Standard Stud:			
Stud Spacing:			
Jamb Section:			
Shear Wall Column:			
Vertical Deflection @ Struct	uro		
· Method	uie		
 VertiClip[®]/VertiTrack[®] Type 	 □ - SL / VTX		-
voracap / vora reach rypo	□ - SLB / SLS / SLT		
Clip Fastening to Stud Web	#12 Screws		
Clip Fastening to Structure	#PAF's / in/mn	n Weld	
Clip Fastening at Jambs to			
Structure	#PAF's / in/mn	n Weld	
Lateral Drift and Vertical De	flaction @ Structure		
Lateral Drift and Vertical De - Method	nection @ Structure		
- Method - DriftClip [®] /DriftTrak [®] Type	□ - DSL/DTSL		
- Dilitolip /Dilititak Type	□ - DSLB/DTSLB/DSLS		
Clip Fastening to Stud Web	#12 Screws		
- Clip Fastening to Structure	#¼-20 Screws	/ PAF	
- Clip Fastening at Jambs		, <u></u>	
To Structure	#1/4-20 Screws	/ PAF	
 DriftTrak[®] to Structure 	#PAF's / in/mn	n weld	
- DriftTrak® Fastener Spacing	in. o.c.		
Stud Bridging			
- Method			
- BridgeBar [®] Type	□ - BB150		
- Cold-Rolled Channel	_ 		
- CRC/FS	Thickness / Wi	dth	
- Connection to Stud			
- Fasteners	#10 Screws		
- Vertical Spacing (max.)	ft. o.c.		
Stud Attachment Bottom Tra	_		
- Method	StiffClip® TD/CL/AL/Screw	<u> </u>	
Anchor to Floor (if req.)			
Fasten to FloorTrack to Stud w/ (2)	#PAF @in/mn Screws	1 O.C	

Condition:	Design Requirement	Drawing Reference	Inspected As-Built
 Standard Header Section² Built-Up Fasteners @ Standard Sill Section³ 	" o.cs utilized)		
Jamb Attachment @ Botto	om Track		
- Method			
 Fasten Track to Floor 	#PAF / Anchors		
 Track to Stud w/ (2) 	Screws ea. Stu	d	
Bracing / Reinforcement - Knee Brace - Joist Plates	Studs ft. o.c	D	
Notes:			

Condition:

		y: ate:		
Interior Non Axial Load	d Bearing Wall Section Design Requirement	:(Architectural Reference) Drawing Reference	Inspected As-Built	
Standard Stud:				
Stud Spacing: Jamb Section:				
Vertical Deflection @ Struc	cture			
- Method				
- Clip Fasten at Web	#8 Screws			
- Fasten to Structure	#PAF @ in/mı	m o.c		
- Fasten at Jambs	#PAF's			
Lateral Drift and Vertical D	eflection @ Structure			
- Method	<u>DriftClip[®] DSLD</u>			
- Clip Fasten at Web	#12 Screws			
- Fasten to Structure				
- Fasten at Jambs	#8 Screws			
Stud Bridging				
- Method	BridgeBar® / CRC / FS			
- BridgeBar [®] Type	□ - ¾" Stud Punchout (BB75□ -1 ½" Stud Punchout (BB15	•		
- CRC/FS	in/mm	, <u> </u>		
- Connection to Stud	BridgeClip [®] / Clip Angle			
- Fasteners	#10 Screws			
- Vertical Spacing (max.)	ft. o.c.			
Stud Attachment Bottom T	rack			
- Fasten Track to Floor	#PAF@in/m	m o.c		
- Track to Stud w/ (2)	Dia. Screws			
Door/Window Openings				
- Jamb Method	Single Section / Built-Up			
- Header Section	Single Section / Built-Up			
- Fasteners @ o.c.*	# Screws			
- Sill Section	Single Section / Built-Up			
- Fasteners @ o.c.*	# Screws			
* Fasteners required only for a h	uilt-up jamb, header, or sill section	ın		
i asteriors required only 101 a D	raint-up jamio, neader, or siii sectio	111.		
			-	

Condition:	Design Requirement	Drawing Reference	Inspected As-Built
Header / Sill Attachment to J	amh		
	StiffClip® HE / AL		
- Method			
- HE Fasten at Web/Jamb*	#10 Screws**		
- AL Fasten at Jamb Web	#10 Screws**		
- AL Fasten at Header/ Sill	#10 Screws**		
Jamb Attachment @ Bottom	Track		
- Fasten Track to Floor	#PAF / Anchors		
	PAR / Anchors		
- Track to Stud w/ (2)		Stud	
* StiffClip® HE used only with a Bui ** Symmetrically Placed Screws	ilt-Up Header		
Notes:			
			<u> </u>
			_
			_
			_

	By: Date:				
Axial Load Bearing Wal	(Architectural Refe	erence) Drawing Reference	Inspected As-Built		
Standard Stud: Stud Spacing: Jamb Section: Shear Wall Column:					
Stud Bridging - Method - BridgeBar® Type - Cold-Rolled Channel - CRC/FS - Solid Blocking Type - Connection to Stud - Fasteners - Vertical Spacing (max.) Stud Attachment Top & B - Method (Select One) - Fasten Track to Top - Fasten Track to Floor - Track to Stud W/ (2)	- BB150 - #10 Screws - #1. o.c. cottom Track StiffClip® TD/CL/AL/Screws - #PAF @in/mm o.c - #PAF @in/mm o.c - Dia. Screws				
 Standard Header Section Built-Up Fasteners @ Standard Sill Section 	_" o.c. ¹				
Header & Sill Attachment - Method - Fasten at Web of Jamb - Fasten at Web of Sill - Fasten at Web of Header Jamb Attachment @ Bott - Method - Fasten Track to Top - Fasten Track to Floor - Track to Stud w/ (2)					

	Date:		
Shear Wall Section:			
(Arch	nitectural Reference)		
Condition:	Design Requirement	Drawing Reference	Inspected As-Built
Method	StiffWall [®]		
Infill Stud Spacing:	in/mm o.c.		
Infill Stud Designation:			
Shear Wall Column Designation			
Built-up Column			
# of Studs # of Tracks			
StiffWall [®] Boot Type	A/B/C/D/F (Heavy)		
Anchor thru Floor/Diameter	TAT BY BY BY I (Houvy)		
Anchor to Foundation			
Embedment Depth			
Diameter Gusset Plate/Strap Track (if require			
Flat Strap Width	eu)		
Flat Strap Thickness	mils		
# of Screws (No. 12)			
Weld (if required)			
Stud Bridging			
- Method			
- BridgeBar [®] Type	□ - BB150		
- Cold-Rolled Channel	-		·
- CRC/FS	Thickness / Width	າ	
Solid Bridging TypeConnection to Stud			
- Fasteners	#10 Screws		
- Vertical Spacing (max.)	ft. o.c.		
Stud Attachment Top & B	ottom Track		
- Fasten Track to Top	#PAF @in/mm	1 O.C.	
- Fasten Track to Floor	#PAF @in/mm	1 O.C.	
- Track to Stud w/ (2)	Dia. Screws		·
Column			
- Method	StiffWall® Column		
- Column Section	Studs Track		
 Fasteners @ 12" o.c.* (* Required if built-up Member) 	#Screw	S	
Column Attachment @ To	n & Bottom		
- Method	StiffWall [®] Boot		
- Boot Type	A / B/ C / D / F (Heavy)		
- Connection @ Top	L		
- Fasten to Structure	# Anchors		
- Connection @ Floor	L		
 Fasten to Floor 	# Anchors		

Condition:	Design Requirement	Drawing Reference	Inspected As-Buil
Standard Joist:			
loist Spacing:			
Girder Section:			
Joist Bridging			
Method	FS / Solid (SI	3)	
Spacing	Feet o.c.		
Connection	L		
Fasteners	#10 Screws		
Joist Attachment @ End	ds		
Fasten to Top	#PAF @in/m	m o.c	
Fasten to Floor	#PAF @in/m		
Track to Joist w/ (2)	Dia. Screws		
Joist Hanger	<u>StiffClip[®] JH</u>		
Joist Clip	StiffClip® JC		
Stair Openings			
Method	JamStud / JamStud and T	<u>rack</u>	·
Header Section	JamStud Tracl	k	
Fasteners @ 12" o.c.	#Screws	S	·
Jamb Section	JamStud Tracl	k	·
Fasteners @ 12" o.c.	#Screv	vs	
Stair Header Attachmei			
Method	StiffClip® AL		
AL Fasten at Web	#12 Screws		
AL Fasten at Joist	#PAF's / in/mm We	ld	
Built-up Girder	.		
Built-up Girder Section	Joist Track		
Fasteners @ 12" o.c.	#Scre	WS	
Angle Conn. @ Ends	L		
Fasteners @ 12" o.c.	# Scre	WS	
Girder Depth:	in/mm		
Member Flange Width's	in/mm		
Material Thickness:	mils		
Notes:			

			By: Date:	
Roof Rafter Plan:(Archi	tectural Reference)			
Condition:	Design Requirement	Drawing Reference	Inspected As-Built	
Standard Joist:				
Joist Spacing:				
Girder Section:				
Rafter Bridging				
Method	FS / Solid (SB))		
Spacing	Feet o.c.			
Connection	L			
Fasteners	#10 Screws			
Rafter Attachment @ End	ls			
Fasten to Top	#PAF @in/m	nm o.c.		
Fasten to Floor	#PAF @in/m			
Track to Rafter w/ (2)	Dia. Screws			
Track to traiter w/ (2)	Dia. Sciews			
Openings (skylight)				
Built-up Header Section	Rafter Track			
Fasteners @ 12" o.c.	# Screws			
Built-up Rafter Section	Rafters Track			
Fasteners @ 12" o.c.	# Screws			
Opening Header Attachm	ent to Built-up Rafter			
- Angle Material	L			
Fasteners @ 12" o.c.	# Screws			
Puilt up Cirdor				
Built-up Girder - Built-up Girder Section	Rafter Track			
Fasteners @ 12" o.c.	# Screws			
				
Angle Connection @ Ends	L			
Fasteners @ 12" o.c.	# Screws			
Girder Depth:	in/mm			
Member Flange Width's	in/mm			
Material Thickness:	mils			
Notes:				
			_	