

Models			CB-CAC/7T/Sc	CB-CAC/8.5T/Sc	CB-CAC/10T/Sc	CB-CAC/15T/Sc	CB-CAC/17T/Sc	CB-CAC/18T/Sc	CB-CAC/37T/Sc	CB-CAC/53T/Sc	CB-CAC/56T/Sc	مدل	
<b>Cooling Capacity</b>		Kw	25	30	35	55	60	65	130	185	195	ظرفیت سرمایشی	
<b>Heating Capacity</b>		Kw	27	32	37	59	64	69	138	200	210	ظرفیت گرمایشی	
<b>POWER SUPPLY</b>		v/ph/Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380-415/3/50	380-415/3/50	منبع تغذیه	
<b>RATE CURRENT</b>	Cooling	A	11.6	16.3	19.1	29.8	32.6	35.4	70.6	110	115	سرمایش	
	Heating	A	13.3	16	18.7	29.2	32	34.8	69.4	107	115	گرمایش	
<b>Compressor</b>	Type	-	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	نوع	
	Quantities	Pieces	1digit+1fixed	1digit+1fixed	1digit+1fixed	2fixed speed	2fixed speed	2fixed speed	4fixed	6fixed	6fixed	اوپراتور	
<b>Power input</b>	Compressor	Cooling	W	7300	8800	10300	16000	17600	19000	40400	61000	65000	سرمایش
		Heating	W	7200	8700	10200	15800	17400	18800	39000	60000	63000	گرمایش
Fan motor		W	670	670	670	650	650	650	880	880	880	موتور فن	
<b>Energy control class</b>		%	10-100	10-100	10-100	100	100	100	100	100	100	کنترل انرژی	
<b>Refrigerant</b>	Type	-	R22	R22	R22	R22	R22	R22	R22	R22	R22	نوع	
	Weight	Kg	7	7	7	15	15	15	28	42	42	وزن	
<b>Condenser air side</b>	Air side exchanger type	-	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	Copper-fin-coil	مدل کوئل	
	Quantities of fan motor	Pieces	1	1	1	2	2	2	4	6	6	تعداد فن بیرونی	
	Air flow volume	-	12000	12000	12000	24000	24000	24000	48000	72000	72000	حجم هوادهی	
	Waterside heat-exchanger type	M3/h	Double tube	Double tube	Double tube	Shell and tube	Shell and tube	Shell and tube	Shell and tube	Shell and tube	Shell and tube	اوپراتور	
<b>Evaporator waterside</b>	Water resistance loss	Lpa	20	20	20	15	15	15	17.5	30	30	مقاومت	
	Water inlet/outlet pipe line	mm	40	40	40	100	100	100	65	65	65	سایز لوله ها	
	Water flow volume	M3/h	4.4	5.2	5.9	9.4	10.3	11.2	22.4	34.4	36.1	حجم جریان آب	
	Max pressure	Mpa	1	1	1	1	1	1	1	1	1	حداکثر فشار	
	Water pipe connection type	-	Soft connection	Soft connection	Soft connection	Soft connection	Soft connection	Soft connection	Soft connection	Soft connection	Soft connection	لوله اتصال	
<b>dimension</b>	L*W*H	Net	mm	1514*850*1820	1514*850*1820	1514*850*1820	2000*900*1880	2000*900*1880	2000*900*1880	2000*1700*1940	2850*2000*2130	2850*2000*2130	خالص
		Packing	mm	1620*1034*2041	1620*1034*2041	1620*1034*2041	2090*905*2020	2090*905*2020	2090*905*2020	2090*1785*2060	3980*2135*2270	3980*2135*2270	بسته بندی
<b>Weight</b>	Net Weight	kg	380	380	380	580	580	580	1080	1730	1750	وزن خالص	
	Operating weight	kg	400	400	400	650	650	650	1200	2000	2100	عامل وزن	
<b>Control type</b>		-	Wired control	Wired control	Wired control	Wired control	Wired control	Wired control	Wired control	Wired control	Wired control	نوع کنترل	
<b>Safely protection device</b>		Switch, water-flow, over-load, ses sequence protection										محافظه دستگاه	
<b>Electric heater (optional)</b>	Power supply	b/ph/hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380-415/3/50	380-415/3/50	منبع تغذیه	
	Power input	kw	7.5	7.5	7.5	15	15	15	30	45	45	هیتز برقی (سفارشی) برقی ورودی	