

Turbo HD Camera



دوربین های آنالوگ Turbo HD سری CO از سری جدید دوربین های هایک ویژن با قابلیت های زیر

- 1.0 Megapixel high-performance CMOS
- Analog HD output, 720P
- True Day/Night
- DNR (Digital Noise Reduction)
- Smart IR
- 3.6mm Lens



DS-2CE56C0T-IRMM	DS-2CE56C0T-IR	DS-2CE56C0T-IRM	DS 2CE56 C0T IT1	DS 2CE56 C0T IT3
				
➤ 20m IR distance ➤ Indoor	➤ 20m IR distance ➤ IP66 weatherproof	➤ 20m IR distance ➤ IP66 weatherproof	➤ 30m IR distance ➤ IP66 weatherproof ➤ 2.8,3.6,6 mm Lens	➤ 50m IR distance ➤ IP66 weatherproof ➤ 2.8,3.6,6 mm Lens
1,160,000	1,280,000	1,400,000	1,670,000	1,910,000

DS-2CE16C0T-IR	DS-2CE16C0T-IT1	DS-2CE16C0T-IT3	DS-2CE16C0T-IT5
			
➤ 20m IR distance ➤ IP66 weatherproof	➤ 30m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ IP66 weatherproof ➤ 3.6,6,8 mm Lens	➤ 80m IR distance ➤ IP66 weatherproof ➤ 3.6,6,8 mm Lens
1,400,000	1,670,000	1,910,000	2,800,000



دوربین های آنالوگ Turbo Full HD سری D0 از سری جدید دوربین های هایک ویژن با قابلیت های زیر

- 2 Megapixel high-performance CMOS
- Analog Full HD output, 1080P
- True Day/Night
- Private Mask Up to 8 zones
- Motion Detection Up to 4 zones
- OSD menu controlled via Coaxial Cable
- Anti-flicker , AGC , BLC
- 3D DNR, DWDR (Digital Wide Dynamic Range) , Smart IR
- IP66 weatherproof



DS-2CE16D0T-IR	DS-2CE16D0T-IT1	DS-2CE16D0T-IT3	DS-2CE16D0T-IT5
			
➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 20m IR distance ➤ 3.6,6 mm Lens	➤ 40m IR distance ➤ 3.6,6,8 mm Lens	➤ 80m IR distance ➤ 3.6,6,8 mm Lens
1,790,000	2,120,000	2,290,000	2,630,000

DS-2CE56D0T-IR	DS-2CE56D0T-IRM	DS-2CE56D0T-IT1	DS-2CE56D0T-IT3
			
➤ 20m IR distance ➤ IP66 weatherproof	➤ 20m IR distance ➤ IP66 weatherproof	➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 20m IR distance ➤ 3.6,6,8 mm Lens
1,670,000	1,790,000	2,120,000	2,290,000

دوربین های آنالوگ **Turbo Full HD** سری **D1** از سری جدید دوربین های هایک ویژن با قابلیت های زیر

- 2 Megapixel high-performance CMOS
- Analog Full HD output, 1080P
- True Day/Night
- Private Mask Up to 8 zones
- Motion Detection Up to 4 zones
- OSD menu controlled via Coaxial Cable
- Anti-flicker , AGC , BLC
- 3D DNR, DWDR (Digital Wide Dynamic Range) , Smart IR
- IP66 weatherproof



DS-2CE16D1T-VFIR3	DS-2CE56D1T-VFIR3
	
➤ 40m IR distance ➤ 2.8~12 Vari - focal lens	➤ 40m IR distance ➤ 2.8~12 Vari - focal lens
3,860,000	3,800,000

دوربین های آنالوگ **Turbo Full HD** سری **D7** از سری جدید دوربین های هایک ویژن دارای **WDR True** با قابلیت های زیر

- 2 Megapixel high-performance CMOS
- Analog Full HD output, 1080P
- **True WDR**, up to 120dB
- True Day/Night
- Private Mask Up to 8 zones
- Motion Detection Up to 4 zones
- OSD menu controlled via Coaxial Cable
- Anti-flicker , AGC , BLC
- 3D DNR, DWDR (Digital Wide Dynamic Range) , Smart IR
- IP66 weatherproof



DS-2CE16D7T-IT	DS-2CE16D7T-IT1	DS-2CE16D7T-IT3	DS-2CE16D7T-IT5	DS-2CE16D7T-IT3Z
				
➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens	➤ 80m IR distance ➤ 6,8,12 mm Lens	➤ 40m IR distance ➤ 2.8~12 Vari - focal lens ➤ Motorized
2,610,000	2,910,000	3,090,000	3,460,000	5,150,000

DS-2CE56D7T-ITM	DS-2CE56D7T-IT1	DS-2CE56D7T-IT3	DS-2CE56D7T-IT3Z
			
➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 40m IR distance ➤ 3.6,6,8 mm Lens	➤ 40m IR distance ➤ 2.8~12 Vari - focal lens ➤ Motorized
2,610,000	2,790,000	3,030,000	5,030,000

دوربین های آنالوگ **3 Turbo Full HD** مگا پیکسل سری **F1** از سری جدید دوربین های هایک ویژن با قابلیت های زیر

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- Video Frame Rate: 1920 × 1536@18fps
- True Day/Night
- Private Mask Up to 8 zones
- Motion Detection Up to 4 zones
- OSD menu controlled via Coaxial Cable
- Anti-flicker, AGC, BLC, DWDR
- 3D DNR, DWDR (Digital Wide Dynamic Range), Smart IR
- IP66 weatherproof



DS-2CE16F1T-IT	DS-2CE16F1T-IT1	DS-2CE16F1T-IT3	DS-2CE16F1T-IT5
			
➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens	➤ 80m IR distance ➤ 6,8,12 mm Lens
2,700,000	3,020,000	3,200,000	3,580,000

DS-2CE56F1T-ITM	DS-2CE16F1T-IT1	DS-2CE16F1T-IT3
		
➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens
2,700,000	2,890,000	3,140,000

دوربین های آنالوگ Turbo Full HD 3 مگا پیکسل سری F7 از سری جدید دوربین های هایک ویژن با قابلیت های زیر

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- Video Frame Rate: 1920 × 1536@18fps
- True WDR, up to 120dB
- True Day/Night
- Private Mask Up to 8 zones
- Motion Detection Up to 4 zones
- OSD menu controlled via Coaxial Cable
- Anti-flicker , AGC , BLC
- 3D DNR, DWDR (Digital Wide Dynamic Range) , Smart IR
- IP66 weatherproof



DS-2CE16F7T-IT	DS-2CE16F7T-IT3	DS-2CE16F7T-IT5	DS-2CE16F7T-IT3Z
			
➤ 20m IR distance ➤ 3.6,6,8 mm Lens	➤ 50m IR distance ➤ 3.6,6,8 mm Lens	➤ 80m IR distance ➤ 6,8,12 mm Lens	➤ 40m IR distance ➤ 2.8~12 Vari - focal lens ➤ Motorized
4,450,000	4,700,000	4,950,000	7,590,000

DS-2CE56F7T-IT3	DS-2CE56F7T-IT3Z
	
➤ 40m IR distance ➤ 6,8,12 mm Lens	➤ 40m IR distance ➤ 2.8~12 Vari - focal lens ➤ Motorized
4,700,000	6,780,000



DVR

DVR آنالوگ Turbo HD سری 71xxHGHI-E1 با قابلیت های زیر

<< این DVR مخصوص دوربین های سری C0 و دوربین های آنالوگ قدیمی می باشد.>>

- 720P Mini 1U Turbo HD DVR
- Connectable HD-TVI and Analog cameras Self-adaptive access
- Up to full channel @ 720P resolution real-time recording
- 1-ch Audio Input
- HDMI and VGA output at up to 1920*1080P resolution
- Provide 1 SATA interface for HDD with **up to 6TB** capacity
- 4/8/16-ch synchronous playback at 720P resolution and reverse playback for multi-camera
- Customization of tags, searching and playing back by tags
- Support **Hi-DDNS** (HikVision Dynamic Domain Name System) and **EZVIZ** Cloud P2P
- 10M / 100M self-adaptive Ethernet interface, 2 USB2.0

DS-7104HGHI-E1	DS-7108HGHI-E1	DS-7116HGHI-E1
		
➤ 4 channels	➤ 8 channels	➤ 16 channels
3,520,000	5,170,000	7,590,000