


Article | [Open Access](#) | Published: 23 March 2022

Estimating the density of deep eutectic solvents applying supervised machine learning techniques

Mohammadjavad Abdollahzadeh, Marzieh Khosravi, Behnam Hajipour Khire Masjidi, Amin Samimi Behbahan, Ali Bagherzadeh, Amir Shahkar & Farzad Tat Shahdost 

Scientific Reports **12**, Article number: 4954 (2022)

331 Accesses | **1** Altmetric | [Metrics](#)

Abstract

Deep eutectic solvents (DES) are recently synthesized to cover limitations of conventional solvents. These green solvents have wide ranges of potential usages in real-life applications. Precise measuring or accurate estimating thermophysical properties of DESs is a prerequisite for their successful applications. Density is likely the most crucial affecting characteristic on the solvation ability of DESs. This study utilizes seven machine learning techniques to estimate the density of 149 deep eutectic solvents. The density is anticipated as a function of temperature, critical pressure and temperature, and acentric factor. The LSSVR (least-squares support vector regression) presents the highest accuracy among 1530 constructed intelligent estimators. The LSSVR predicts 1239 densities with the mean absolute percentage error (MAPE) of 0.26% and $R^2 = 0.99798$. Comparing the LSSVR and four empirical correlations revealed that the earlier possesses the highest accuracy level. The prediction accuracy of the LSSVR (i.e., MAPE = 0.26%) is 74.5% better than the best-obtained results by the empirical correlations (i.e., MAPE = 1.02%).

Introduction

environmental protection⁶. The separation process primary responsibility is to remove contaminants from feed stocks and effluent liquid and gas streams, purify final products, and recover unreacted materials⁷. Although diverse separation processes have already been established, the solvent-based technique has a wider range of applications.

The green chemistry principles introduced by Anastas and Warner suggested constructing chemical processes that eliminate or at least reduce utilizing/generating harmful substances⁸. Since the traditional organic solvents undesirably impact the ecosystem and human health, researchers have paid great attention to synthesizing green, sustainable, and environmentally-friendly solvents. Attempts to fulfill this objective have resulted in suggesting supercritical fluids⁹, renewable solvents¹⁰, liquid polymers¹¹, and ionic liquids¹².

Deep eutectic solvents (DES) have recently been recommended as materials that have the favorable features of ionic liquids and cover their undesirable characteristics^{13,14,15,16}. Deep eutectic solvents have readily been synthesized by mixing two main agents, i.e., hydrogen bond donor (HBD) and hydrogen bond acceptor (HBA)¹⁷. Hydrogen bond formations between HBA and HBD resulted in synthesizing a mixture with a melting point highly smaller than its ingredient¹⁷. Generally, deep eutectic solvents are biodegradable, inexpensive, non-toxic, non-volatile, thermally/chemically stable, and easy to manufacture¹⁷.

Despite a short life of deep eutectic solvents, they have engaged in diverse applications, including material synthesis¹⁸, separation processes¹³, nanotechnology¹⁹, environmental protection¹⁷, biotechnology²⁰, and pharmaceutical processing²¹.

The accurate values of volumetric properties of deep eutectic solvents, like density, are essential for feasibility study and detailed design of any possible industrial usages of DESs²². Moreover, selecting an appropriate DES with the desired density is an arduous task to be accomplished through laboratory-scale investigations.

technically been built for estimating the density of DESs (see Sect. 3.1), to the best of our knowledge, no intelligent scheme has been suggested yet. Hence, this work utilizes five intelligent schemes for calculating the DES's density from some available variables, i.e., temperature and DES's inherent features (acentric factor and critical pressure and temperature) and compares their prediction accuracy. This is the most comprehensive modeling study yet conducted for mechanizing the DES's characterization. The databank includes massive laboratory-scale density measurements gathered from the literature to certify that the suggested paradigms are general and robust. The reliability of the constructed intelligent estimators is higher than the other correlations proposed in the literature.

Laboratory-measured datasets

The objective of the current study is constructing an intelligent tool to approximate the density of deep eutectic solvents precisely. Identical to the regression-based correlation²³, all intelligent methods also need a laboratory-measured database to adjust their parameters and test their prediction reliability^{24,25}. Thus, 1239 experimentally measured datasets for the density of deep eutectic solvents have been gathered from thirty references and engaged in the model development/validation stage. The summary of the collected density data has been presented in Table 1. This table introduces the name of hydrogen bond donors and hydrogen bond acceptors of the considered deep eutectic solvents. As Table 1 shows, the gathered databank includes thirteen HBA and forty-two HBD ingredients. This table also indicates the number of measurements and ranges of the working temperature and measured density.

Table 1 Summary of the reported laboratory-measured density for diverse deep eutectic solvents in the literature.

eutectic solvents. Therefore, it is mandatory to include inherent characteristics of these materials in the list of independent variables. The three-parameter corresponding state theory explains that each material has its own specific acentric factor, critical temperature, and critical pressure²⁶. Hence, these parameters could help the machine learning method distinguish different deep eutectic solvents and discriminate among their density values²⁷. Haghbakhsh et al.²⁸ utilized the improved Lydersen-Joback-Reid group contribution¹² and the Lee-Kesler mixing rules²⁹ to estimate acentric factor and critical temperature/pressure of different deep eutectic solvents.

Table 2 presents the range of these inherent characteristics for all considered deep eutectic solvents²⁸. The supplementary excel files includes all experimental databank utilized in the current study.

Table 2 The reported critical pressure, critical temperature, and acentric factor for the considered deep eutectic solvents²⁸.

In order to reduce the table size, the reported values have been presented for deep eutectic solvents based on their hydrogen bond acceptor type. Specific values of the acentric factor, critical temperature, and critical pressure for each deep eutectic solvent can be found in Haghbakhsh et al. article²⁸.

Estimation scenarios for density of deep eutectic solvents

The literature has suggested several empirical correlations for estimating the liquid's density. Furthermore, the current study focuses on seven machine learning methods to anticipate the density of 149 deep eutectic solvents. The mathematical formulation/background of the available empirical correlations and machine learning methods has been briefly reviewed in this section.

Empirical correlations Rackett correlation

function of temperature (T) and critical pressure (P_c), molar volume (ν_c), and temperature (T_c). R and T_r show the gas constant and reduced temperature (Eq. 2), respectively.

$$\nu = \left(\frac{RT_c}{P_c} \right) \left(\frac{P_c \nu_c}{RT_c} \right)^{\left\{ 1 + \left(1 - T_r \right) \right\}^{0.2857}}$$

(1)

$$T_r = T/T_c$$

(2)

Equation (3) is then possible to be used to reach the density (ρ) from the molecular weight (M) and estimated molar volume.

$$\rho = M/\nu$$

(3)

Although Rackett's correlation was initially suggested for the saturated liquid's density, it has also presented good predictions for the deep eutectic solvent⁵⁵.

Spencer and Danner correlation

Spencer and Danner incorporate a base molar volume measurement (ν_{ref}) at a base temperature (T_{ref}) in Rackett's correlation⁵⁶. Equations (4) and (5) introduce the modified Rackett model, i.e., the Spencer and Danner correlation.

$$\nu = \nu_{ref} Z^{\left\{ \left(1 - T_r \right) \right\}^{0.2857 - \left[1 - \left(T_{ref} / T_c \right) \right] \right\}^{0.2857}}}$$

(4)

(5)

Mjalli et al. correlation

Mjalli et al.⁵⁷ suggested a technical correlation for the density of deep eutectic solvents by reformulating the Spencer and Danner model. Equations (6) and (7) express the mathematical shape of the developed correlation by Mjalli et al.⁵⁷.

$$\rho = \rho_{ref} Z^{\left\{ \left(1 - T_r \right)^{2.2857 - \left[1 - \left(T_{ref} / T_c \right) \right]} \right\}}$$

(6)

$$Z = \left(\rho_{ref} P_c / RT_c \right)^{\left\{ \left[0.2083 + \left(T_{ref} / T_c \right) \right] \right\}}$$

(7)

Hagbakhsh et al. correlation

Hagbakhsh et al. recently proposed a correlation for calculating the density of deep eutectic solvents from the working and critical temperatures, acentric factor (ω), and critical molar volume²⁸.

$$\rho = \alpha - 4.64 \times 10^{-4} \times T$$

(8)

$$\alpha = - 1.13 \times 10^{-6} \times T_c^2 + 2.566 \times 10^{-3} \times T_c + 0.2376 \times \omega^{0.2211} - 4.67 \times 10^{-4} \times \nu_c$$

(9)

liquids density. Since the first three inherent properties (T_c , P_c , and v_c) are related through the following equation, it is unnecessary to utilize all of them.

$$P_c \times \nu_c = R \times T_c \quad (10)$$

Therefore, the current study only utilizes temperature, T_c , P_c , and ω to estimate the DES's density employing different intelligent estimators (Eq. 11).

$$\rho_{\text{pred}}^{\text{DES}} = f\left(T_c^{\text{DES}}, P_c^{\text{DES}}, \omega^{\text{DES}}\right) \quad (11)$$

Computational intelligent methods

Wide ranges of supervised and unsupervised artificial intelligence techniques have been suggested and applied in different modeling studies^{58,59,60,61,62,63}. The working procedures of the used machine learning methods, i.e., least-squares support vector regression (LSSVR), hybrid neuro-fuzzy system, and five types of artificial neural networks have been briefly explained in this section.

Least-squares support vector regression

This intelligent estimator employs a particular equation (i.e., linear, Gaussian, and polynomial kernel function) to transfer original independent variables (ξ) to a multi-dimensional computational domain. The following equation defines these functions.

$$\varphi\left(\xi_i, \xi_j\right) = \left\{ \begin{array}{l} \xi_i^T \xi_j \\ \text{Linear} \\ \left(\xi_i^T \xi_j + \epsilon\right)^\sigma \\ \text{Polynomial} \\ \exp\left(-\left|\xi_i - \xi_j\right|^2 / \delta^2\right) \\ \text{Gaussian} \end{array} \right. \quad (12)$$

The superscript of T shows the transpose operation. In addition, ϵ , σ , and δ are the kernel-related parameters.

It is then possible to linearly relate the dependent (γ) to the independent (χ) variables in this new computational domain utilizing Eq. (13).

$$\gamma_{\text{LSSVR}}(\chi) = w^T \varphi(\chi) + b \quad (13)$$

In Eq. (13), γ_{LSSVR} represents the estimated target by the least-squares support vector regression. Furthermore, w and b are adjustable coefficients of this intelligent model. In summary, the kernel type is the main topology feature of the LSSVR that should be determined by a practical scenario like the trial-and-error process⁶⁴.

The detailed working process of the least-squares support vector machine has recently been explained by Nabavi et al.⁶⁴.

Artificial neural networks

This neuron-based machine learning method is the most widely-used tool as either estimator^{65,66} or classifier⁶⁷. The working process of the artificial neural network is handled by a combination of linear (LPart) and non-linear (NLPart) operations conducted by the neuron as follows⁶⁸:

$$\text{LPart} = \vec{w} \cdot \vec{\xi} + b \quad (14)$$

$$\text{NLPart} = \phi(\vec{w} \cdot \vec{\xi} + b) \quad (15)$$

differentiable ones often provide artificial neural networks with a better generalization ability⁶⁹. Equation (16) defines several widely-used activation functions in the field of artificial neural networks.

$$\phi(LPart) = \left\{ \begin{array}{l} \text{Linear} \\ \frac{1}{1 + \exp(-LPart)} \\ \text{Logarithm\,sigmoid} \\ \frac{2}{1 + \exp(-2 \times LPart)} - 1 \\ \text{Tangent\,sigmoid} \\ \exp(-LPart^2 / 2\delta^2) \\ \text{Gaussian} \end{array} \right.$$

(16)

Different artificial neural networks can be built by inserting neurons in several successive neuron layers. The multilayer perceptron⁷⁰, recurrent^{71,72,73}, cascade feedforward⁷⁰, radial basis function⁷⁰, and general regression⁷⁴ neural networks are those neuron-based estimators utilized in the current study. Interested readers are referred to the book written by Hagan et al. for the detailed understanding of the working procedure of these artificial neural networks⁷⁵.

Hybrid neuro-fuzzy systems

The idea of combining the artificial neural network^{76,77} and fuzzy logic^{78,79} has resulted in a new class of machine learning, namely adaptive neuro-fuzzy inference system^{80,81}. This method estimates a target response employing five successive layers (i.e., fuzzification, rule, normalization, defuzzification, and output)⁸². Shojaei et al. have comprehensively described the mathematical operations performed in each layer of the adaptive neuro-fuzzy inference system⁸². The membership function utilized in the fuzzification layer⁸³, numbers of the cluster⁸⁰, cluster radius⁸⁴, and training algorithm²⁵ are the main structural features that are often regulated by the trial-and-error scenario.

intelligent method for estimating the DES's density and determining its structural features. The accuracy of this smart approach and available correlations in the literature has then been compared. Several numerical and graphical analyses have also been employed for further monitoring the accuracy of the best model for predicting the density of deep eutectic solvents.

Constructing intelligent models **Topology determination**

The topology of machine learning methods is often determined by trial-and-error practice^{85,85,87}. This practical scenario changes the core features of a machine learning scheme and monitors its accuracy in diverse stages of the model development^{88,88,90}. Table 3 specifies the core features of the considered intelligent techniques and their investigation range during the trial-and-error procedure. The literature approved that artificial neural networks with one hidden layer are accurate enough to simulate a wide range of problems^{72,91,91,93}. Consequently, the multilayer perceptron (MLP), recurrent (RNN), cascade feedforward (CFF), general regression (GR), and radial basis function (RBF) have been fabricated with only one hidden layer.

Table 3 The name and range of deciding features of each intelligent estimator during the trial-and-error process.

Selecting the best topology of the intelligent methods

The core features of the machine learning methods have been changed according to the reported values in Table 3, both training and testing stages have been performed, and accuracy has been monitored utilizing several statistical indexes. Various uncertainty criteria, including MAPE (mean absolute percentage error), RMSE (root mean square error), RAPE (relative absolute percentage error), MAE (mean absolute error), and R^2 (regression coefficient), have been utilized to accuracy monitor of the developed intelligent scenarios and selecting the most precise ones.

$$MAPE\% = \left(\frac{100}{n} \right) \times \sum_{i=1}^n \left(\frac{|\rho_{\text{exp}} - \rho_{\text{pred}}|}{\rho_{\text{exp}}} \right)_i$$

(17)

$$MAE = \left(\frac{1}{n} \right) \times \sum_{i=1}^n |\rho_{\text{exp}} - \rho_{\text{pred}}|_i$$

(18)

$$RAPE\% = 100 \times \frac{\sum_{i=1}^n |\rho_{\text{exp}} - \rho_{\text{pred}}|_i}{\sum_{j=1}^n |\rho_{\text{exp}} - \rho_{\text{exp}}^{\text{ave}}|_j}$$

(19)

$$RMSE = \sqrt{\frac{\sum_{i=1}^n (\rho_{\text{exp}} - \rho_{\text{pred}})_i^2}{n}}$$

(20)

$$R^2 = 1 - \frac{\sum_{i=1}^n (\rho_{\text{exp}} - \rho_{\text{pred}})_i^2}{\sum_{i=1}^n (\rho_{\text{exp}} - \rho_{\text{exp}}^{\text{ave}})_i^2}$$

(21)

These equations only need the actual (ρ_{exp}), predicted (ρ_{pred}), and average ($\rho_{\text{exp}}^{\text{ave}}$) density values and numbers of the dataset (n) to measure the accuracy of any constructed model.

function is the best kernel for LSSVR, 2) eleven hidden neurons is the best feature for the MLP, 3) ten hidden neurons provides the CFF with the best performance, 4) spread factor of 0.04312 and 1053 hidden neurons should be used in the GR structure, 5) the RBF is better to construct by spread factor of 1.0526 and eleven hidden neurons, and 6) the ANFIS (adaptive neuro-fuzzy inference systems) with the subtractive clustering membership function, twelve clusters, and hybrid training algorithm has the best performance.

Table 4 The most precise prediction obtained by different intelligent estimators (1053 training and 186 testing datasets).

Although all these prediction accuracies confirm a high level of consistency with the laboratory-measured density, the LSSVR and RBF neural network present the highest and lowest precise results, respectively. For systematical approving this claim, the subsequent analysis has ranked these selected intelligent models based on their prediction accuracy in different stages of model development.

Selecting the best intelligent model using the ranking analysis

The ranking analysis is a well-established procedure to arrange several models based on their performance. The previous step measured the prediction ability of the seven selected intelligent models using five well-known statistical indexes. Now the ranking analysis utilizes the numerical values of these statistical indexes to arrange them from the best to the worst model. Equation (22) indicates that the selected models have been ranked based on their average rankings over five statistical criteria (*indx*).

$$Rank = \text{round}\left(\frac{\sum_{indx = 1}^5 \{Rank_{indx}\}}{5}\right)$$

(22)

Download PDF

models have also been tracked over the whole 1259 datasets. Figure 1 displays the rank order of the LSSVR, artificial neural network models (i.e., MLP, RNN, RBF, CFF, and GR), and ANFIS over three different databases. It can be easily inferred that the LSSVR with the three first ranking places and the RBF neural network with the three seventh ranking places are the best and worst tools for calculating the density of deep eutectic solvents. The ranking order of other constructed models has also displayed in this figure.

Figure 1

 figure 1

The ranking order of the intelligent estimators in different stages of the model development.


In summary, it can be claimed that the LSSVR equipped with the Gaussian kernel function is the most trustful model for calculating the density of deep eutectic

deep eutectic solvents with the MAPE = 0.26%, MAE = 2.94, RMSE = 4.00%, RMSE = 3.03, and $R^2 = 0.99798$.

Validation stage **The LSSVR versus empirical correlations**

The accuracy of the suggested LSSVR and four empirical correlations in the literature (Rackett, Spencer and Danner, Mjalli et al., and Haghbakhsh et al.) for estimating 1239 densities of the deep eutectic solvent has been compared in the current section. The results of this comparison utilizing the MAPE have been described in Fig. 2. The observed results confirm that the LSSVR is the most accurate tool for estimating the density of deep eutectic solvents. The LSSVR anticipates 1239 density samples of 149 deep eutectic solvents with the MAPE = 0.26%, while the most accurate empirical correlation (Spencer and Danner model) presents the MAPE = 1.02% for an entirely similar database. The suggested LSSVR improves the best previously achieved accuracy by more than 74%.

Figure 2



The prediction accuracy of the LSSVR and four empirical correlations in the literature²⁸ to estimate the DES's density of a completely similar database.

Validation using graphical inspections

The anticipated densities by the LSSVR (ρ_{LSSVR}) versus their counterpart experimental values (i.e., cross-plot) have been shown in Fig. 3. This cross-plot separately presents the LSSVR predictions for both learning and testing steps. Two straight lines associated with the relative deviation percent (RD%) of -2% and $+2\%$ have also been added to this figure. Equation (23) expresses the formula of the RD%.

$$RD\% = 100 \times \left[\frac{|\rho_{\text{exp}} - \rho_{\text{LSSVR}}|}{\rho_{\text{exp}}} \right] \quad i = 1, 2, \dots, n$$

(23)

Figure 3

The consistency between experimental values of DES's density and the LSSVR's prediction.

Figure 3 displays that about ten density samples have been anticipated with the RD% of lower than -2% and higher than $+2\%$. The excellent ability of the built LSSVR to estimate the density of deep eutectic solvents can be readily approved by this observation.

The kernel density estimation is a reliable method for visually inspecting the compatibility between a given variable's actual and anticipated values. As Fig. 4 shows, this method depicts the cumulative distribution function (CDF) as a function of the experimental values of a given variable. Figure 4A–C illustrate the compatibility between actual and anticipated density values over the training and testing subdivisions and the whole database. Excluding the intermediate values of the DES's density, a remarkable consistency can be seen between actual and predicted values.

Figure 4

 figure 4

Utilizing the kernel density estimation method to check the LSSVR validity in the training (**A**) and testing (**B**) stages and against whole the databank (**C**).

The magnitude of difference between actual and predicted densities (the residual error, i.e., RE) is another statistical index applied to monitor the prediction accuracy of the built LSSVER. The mathematical expression of the RE is given in Eq. (24).

$$RE_{i} = \left(\rho_{\exp} - \rho_{\text{LSSVR}} \right)_{i} \quad i = 1, 2, \dots, n$$

Based on reported results in Fig. 5, 61% of the available samples have been estimated with a residual error of less than 2 kg/m^3 . Moreover, the LSSVR successfully anticipated 84% of the experimental databank with an RE of lower than 5 kg/m^3 . Only 16% of the gathered database has been estimated with a residual error of higher than 5 kg/m^3 . All these observations confirm the excellent compatibility between calculated densities by the LSSVR and their related actual measurements.

Figure 5

 figure 5

The cumulative frequency of the residual error (RE) of the LSSVR for estimating the DES's density.

Checking the reliability of the gathered database

The gathered experimental data had a central role during the development/validation/selection of machine learning methods hereinbefore. Furthermore, this experimental databank has been used to compare the accuracy of empirical correlations and the selected LSSVR. The entire previous findings are valid only if the gathered laboratory-measured densities have an acceptable validity level.

(SR) against the Hat index to accomplish its duty . Equation (27) explains that the SR can be obtained by dividing the average value (\overline{RE}) and standard deviation (SD) of the residual error. Equations (25) and (26) give the \overline{RE} and SD formula, respectively.

$$\overline{RE} = \left(\frac{1}{n} \right) \times \sum_{i=1}^n RE_i$$

(25)

$$SD = \sqrt{\sum_{i=1}^n \left(RE_i - \overline{RE} \right)^2 / n}$$

(26)

$$SR_i = RE_i / SD \quad ; i = 1, 2, \dots, n$$

(27)

Furthermore, numerical values of the Hat index (HI) can be reached by applying Eq. (28) on the matrix of the independent variables (ξ)⁹⁵. The superscripts of T and -1 stand for the transpose and inverse operations, respectively.

$$HI = \xi \left(\xi^T \xi \right)^{-1}$$

(28)

Figure 6 shows the plot of SR versus the HI values associated with the DES's density databank. The leverage method states that the region bounded by the $-3 < SR < +3$ and HI lower than the critical leverage is valid, and all other positions are the suspect domain⁹⁶. Equation (29) helps calculate the critical leverage (CL) from the number of independent variables (NIV) and experimental data points (n)^{83,95}. Having four independent variables and 1239 data points, the CL equals 0.0121.

Figure 6

 figure 6

The results of applying the leverage method on the gathered density databank.

The leverage method approves that 1210 out of 1239 data points have appeared in the valid zone, and only 29 density samples may be outlier measurements. It can be claimed that the validity of the gathered database has been approved now, and all previous findings based on this databank are trustful.

LSSVR accuracy for density predicting each deep eutectic solvent

(Eq. 30) claims both underestimated and overestimated predictions, it has been selected to measure the LSSVR accuracy in this stage.

$$ARD\% = \left(\frac{100}{n} \right) \times \sum_{i=1}^n \left[\left(\frac{|\rho_{\text{exp}} - \rho_{\text{LSSVR}}|}{\rho_{\text{exp}}} \right) \right]_i$$

(30)

Figure 7 states that the density of thirteen classes of the deep eutectic solvent with the HBA#1 to HBA#13 (see Table 1) has been estimated with the ARD ranges from - 0.24 to + 0.17%. Those deep eutectic solvents having the HBA #1, 9, and 13 have been underestimated by the LSSVR. On the other hand, the DESs with the HBA #3, 5, and 12 have been overestimated. The ARD% associated with the other deep eutectic solvent classes is almost equal to zero.

Figure 7

The observed average relative deviation between actual and predicted densities of the deep eutectic solvent with the same HBA agent.

Investigating the effect of temperature, and HBD/HBA types

The effect of temperature on the density of deep eutectic solvents with the specific HBA agent (i.e., Choline chloride) and different HBD substances can be deduced from Fig. 8. This figure reports both experimentally-measured densities and their counterparts simulated values by the LSSVR. This figure readily justifies an excellent agreement between experimental and predicted density values. The LSSVR effectively discriminates between the effect of HBD type and working temperature on the density of the Choline chloride-based DESs and accurately estimates all distinct data points. Like the conventional liquid, the density of deep eutectic solvents decreases by increasing the working temperature. Increasing the intermolecular void volume in the DES's body by increasing the temperature has been introduced as responsible for this observation⁹⁸.

Figure 9

The excellent performance of the LSSVR model for correctly identifying the HBD effect on the density of Choline chloride as an HBA.

The density variation of deep eutectic solvents with the temperature and HBA type has been exhibited in Fig. 9. All DESs in this analysis have glycerol as their HBD agent. A high level of compatibility between actual density values and their counterparts estimated by the LSSVR can be seen in Fig. 9. The LSSVR distinguishes the effect of HBA type and temperature on the DES's density and accurately anticipates all individual density data points.

Figure 9

Monitoring the ability of the LSSVR model to anticipate the HBA effect on the density of the glycerol as an HBD.

Simple flowchart of our study

A simple and understandable flowchart for the stages followed in the current research study has been presented in Fig. 10. This figure can be broken down into four distinct parts as follows:

1. Developing machine learning methods
2. Comparing accuracy performances of the machine learning methods and empirical correlations
3. Selecting the model with the highest prediction accuracy

Figure 10

 figure 10

A simple flowchart for explaining the stages followed in the present study.

Conclusion

The accuracy of seven machine learning methods and four empirical correlations has been compared to find the highest accurate tool for estimating the density of 149 deep eutectic solvents. Huge performed statistical analyses proved that the least-squares support vector regression equipped with the Gaussian kernel function is more accurate than the other methods investigated. This suggested scheme predicted 1239 experimentally-measured densities with the MAPE = 0.26%, MAE = 2.94, RAPE = 4.06%, RMSE = 5.65, and $R^2 = 0.99798$. Visual inspections utilizing the cross-plot, kernel density estimation, residual error, and average relative deviation have also justified a high level of compatibility between LSSVR predictions and their experimentally-measured counterparts. Investigating the experimental database employing the leverage technique resulted in founding 1210 valid and 29 suspect information. Furthermore, the fabricated LSSVR successfully infers the effect of temperature and HBA and HBD types on the density of the deep eutectic solvent. The current research

design and simulate new processes utilizing the DLS.

Data availability

All data generated or analyzed during this study are included in the supplementary file.

References

1. Pianko-Oprych, P., Hosseini, S. M. & Jaworski, Z. Model development of integrated CPOx reformer and SOFC stack system. *Polish J. Chem. Technol.* **18**, 41–46 (2016).
2. Seaberg, J., Kaabipour, S., Hemmati, S. & Ramsey, J. D. A rapid millifluidic synthesis of tunable polymer-protein nanoparticles. *Eur. J. Pharm. Biopharm.* **154**, 127–135 (2020).
3. Vaferi, B., Bahmani, M., Keshavarz, P. & Mowla, D. Experimental and theoretical analysis of the UV/H₂O₂ advanced oxidation processes treating aromatic hydrocarbons and MTBE from contaminated synthetic wastewaters. *J. Environ. Chem. Eng.* **2**, 1252–1260 (2014).
4. GhanbariPakdehi, S. & Vaferi, B. A study on adsorptive removal of DMAZ from aqueous solutions by ZSM-5, NaY zeolites, and activated carbon: kinetic and isotherm. *Desalin. Water Treat.* **57**, 18286–18292 (2016).
5. Jahanmahin, O., Rahmati, M. M. M., Mohammadi, T., Babaei, J. & Khosravi, A. Cr (VI) ion removal from artificial waste water using supported liquid membrane. *Chem. Pap.* **70**, 913–925 (2016).

MEMBRANE REACTOR FOR METHANOL SYNTHESIS. *Appl. Energy*. **88**, 41–51 (2011).

7. P.C. Wankat, Separation process engineering: includes mass transfer (2012).

8. Anastas, P. T. & Warner, J. C. Green chemistry. *Front. (Boulder)*. **640**, 1998 (1998).

9. Lashkarbolooki, M., Vaferi, B., Shariati, A. & Zeinolabedini Hezave, A. Investigating vapor-liquid equilibria of binary mixtures containing supercritical or near-critical carbon dioxide and a cyclic compound using cascade neural network. *Fluid Phase Equilib.* **343**, 24–29 (2013).

10. Rasool, M. A. & Vankelecom, I. F. J. Use of γ -valerolactone and glycerol derivatives as bio-based renewable solvents for membrane preparation. *Green Chem.* **21**, 1054–1064 (2019).

11. Chen, J., Spear, S. K., Huddleston, J. G. & Rogers, R. D. Polyethylene glycol and solutions of polyethylene glycol as green reaction media. *Green Chem.* **7**, 64–82 (2005).

12. Valderrama, J. O., Sanga, W. W. & Lazzús, J. A. Critical properties, normal boiling temperature, and acentric factor of another 200 ionic liquids. *Ind. Eng. Chem. Res.* **47**, 1318–1330 (2008).

13. Deng, D., Liu, X. & Gao, B. Physicochemical properties and investigation of azole-based deep eutectic solvents as efficient and reversible SO₂ absorbents. *Ind. Eng. Chem. Res.* **56**, 13850–13856 (2017).

14. Florindo, C., Oliveira, M. M., Branco, L. C. & Marrucho, I. M. Carbohydrates-based

15. Liu, X., Gao, B., Jiang, Y., Ai, N. & Deng, D. Solubilities and thermodynamic properties of carbon dioxide in guaiacol-based deep eutectic solvents. *J. Chem. Eng. Data.* **62**, 1448–1455 (2017).
16. Li, G., Jiang, Y., Liu, X. & Deng, D. New levulinic acid-based deep eutectic solvents: synthesis and physicochemical property determination. *J. Mol. Liq.* **222**, 201–207 (2016).
17. Ghaedi, H., Ayoub, M., Sufian, S., Lal, B. & Shariff, A. M. Measurement and correlation of physicochemical properties of phosphonium-based deep eutectic solvents at several temperatures (293.15 K–343.15 K) for CO₂ capture. *J. Chem. Thermodyn.* **113**, 41–51 (2017).
18. Carriazo, D., Serrano, M. C., Gutiérrez, M. C., Ferrer, M. L. & del Monte, F. Deep-eutectic solvents playing multiple roles in the synthesis of polymers and related materials. *Chem. Soc. Rev.* **41**, 4996–5014 (2012).
19. Zhao, B.-Y. *et al.* Biocompatible deep eutectic solvents based on choline chloride: characterization and application to the extraction of rutin from *Sophora japonica*. *ACS Sustain. Chem. Eng.* **3**, 2746–2755 (2015).
20. Mbous, Y. P. *et al.* Applications of deep eutectic solvents in biotechnology and bioengineering: promises and challenges. *Biotechnol. Adv.* **35**, 105–134 (2017).
21. Emami, S. & Shayanfar, A. Deep eutectic solvents for pharmaceutical formulation and drug delivery applications. *Pharm. Dev. Technol.* **25**, 779–796 (2020).

-
23. Taherzadeh, M., Haghbakhsh, R., Duarte, A. R. C. & Raeissi, S. Estimation of the heat capacities of deep eutectic solvents. *J. Mol. Liq.* **307**, 112940 (2020).
-
24. Mahmoodi, F., Darvishi, P. & Vaferi, B. Prediction of coefficients of the Langmuir adsorption isotherm using various artificial intelligence (AI) techniques. *J. Iran. Chem. Soc.* **15**, 2747–2757 (2018).
-
25. Karimi, M., Aminzadehsarikhanbeglou, E. & Vaferi, B. Robust intelligent topology for estimation of heat capacity of biochar pyrolysis residues. *Measurement* **183**, 109857 (2021).
-
26. Privat, R., Moine, E., Sirjean, B., Gani, R. & Jaubert, J.-N. Application of the corresponding-state law to the parametrization of statistical associating fluid theory (SAFT)-type models: generation and use of “generalized charts”. *Ind. Eng. Chem. Res.* **58**, 9127–9139 (2019).
-
27. He, S., Guo, F., Zou, Q. & Ding, H. MRMD2.0: A python tool for machine learning with feature ranking and reduction. *Curr. Bioinform.* **15**, 1–9 (2020).
-
28. Haghbakhsh, R., Bardool, R., Bakhtyari, A., Duarte, A. R. C. & Raeissi, S. Simple and global correlation for the densities of deep eutectic solvents. *J. Mol. Liq.* **296**, 111830 (2019).
-
29. Knapp, H., Zeck, S., & Langhorst, R. Vapor-liquid equilibria for mixtures of low boiling substances. Pt. 3. Ternary systems (1989).
-

31. Sánchez, P. B., González, B., Salgado, J., Parajó, J. J. & Domínguez, Á. Physical properties of seven deep eutectic solvents based on l-proline or betaine. *J. Chem. Thermodyn.* **131**, 517–523 (2019).
32. Yadav, A., Kar, J. R., Verma, M., Naqvi, S. & Pandey, S. Densities of aqueous mixtures of (choline chloride+ ethylene glycol) and (choline chloride+ malonic acid) deep eutectic solvents in temperature range 283.15–363.15 K. *Thermochim. Acta.* **600**, 95–101 (2015).
33. Harifi-Mood, A. R. & Buchner, R. Density, viscosity, and conductivity of choline chloride+ ethylene glycol as a deep eutectic solvent and its binary mixtures with dimethyl sulfoxide. *J. Mol. Liq.* **225**, 689–695 (2017).
34. Florindo, C., Oliveira, F. S., Rebelo, L. P. N., Fernandes, A. M. & Marrucho, I. M. Insights into the synthesis and properties of deep eutectic solvents based on cholinium chloride and carboxylic acids. *ACS Sustain. Chem. Eng.* **2**, 2416–2425 (2014).
35. Yadav, A., Trivedi, S., Rai, R. & Pandey, S. Densities and dynamic viscosities of (choline chloride+ glycerol) deep eutectic solvent and its aqueous mixtures in the temperature range (283.15–363.15) K. *Fluid Phase Equilib.* **367**, 135–142 (2014).
36. Lu, M. *et al.* Solubilities of carbon dioxide in the eutectic mixture of levulinic acid (or furfuryl alcohol) and choline chloride. *J. Chem. Thermodyn.* **88**, 72–77 (2015).
37. Guo, W., Hou, Y., Ren, S., Tian, S. & Wu, W. Formation of deep eutectic solvents by

-
38. Zhu, J. *et al.* Physicochemical properties of deep eutectic solvents formed by choline chloride and phenolic compounds at T=(293.15 to 333.15) K: The influence of electronic effect of substitution group. *J. Mol. Liq.* **232**, 182–187 (2017).
-
39. Yadav, A. & Pandey, S. Densities and viscosities of (choline chloride+ urea) deep eutectic solvent and its aqueous mixtures in the temperature range 293.15 K to 363.15 K. *J. Chem. Eng. Data.* **59**, 2221–2229 (2014).
-
40. Chemat, F., Anjum, H., Shariff, A. M., Kumar, P. & Murugesan, T. Thermal and physical properties of (Choline chloride+ urea+ l-arginine) deep eutectic solvents. *J. Mol. Liq.* **218**, 301–308 (2016).
-
41. Haghbakhsh, R. & Raeissi, S. Densities and volumetric properties of (choline chloride+ urea) deep eutectic solvent and methanol mixtures in the temperature range of 293.15–323.15 K. *J. Chem. Thermodyn.* **124**, 10–20 (2018).
-
42. Haghbakhsh, R. & Raeissi, S. Investigation of solutions of ethyl alcohol and the deep eutectic solvent of Reline for their volumetric properties. *Fluid Phase Equilib.* **472**, 39–47 (2018).
-
43. Chen, Y. *et al.* Solubilities of carbon dioxide in eutectic mixtures of choline chloride and dihydric alcohols. *J. Chem. Eng. Data* **59**, 1247–1253 (2014).
-
44. Craveiro, R. *et al.* Properties and thermal behavior of natural deep eutectic solvents. *J. Mol. Liq.* **215**, 534–540 (2016).
-

-
46. Mjalli, F. S. & Ahmad, O. Density of aqueous choline chloride-based ionic liquids analogues. *Thermochim. Acta.* **647**, 8–14 (2017).
-
47. Shahbaz, K., Baroutian, S., Mjalli, F. S., Hashim, M. A. & AlNashef, I. M. Densities of ammonium and phosphonium based deep eutectic solvents: prediction using artificial intelligence and group contribution techniques. *Thermochim. Acta.* **527**, 59–66 (2012).
-
48. Leron, R. B., Soriano, A. N. & Li, M. H. Densities and refractive indices of the deep eutectic solvents (choline chloride+ ethylene glycol or glycerol) and their aqueous mixtures at the temperature ranging from 298.15 to 333.15 K. *J. Taiwan Inst. Chem. Eng.* **43**, 551–557 (2012).
-
49. Kareem, M. A., Mjalli, F. S., Hashim, M. A. & AlNashef, I. M. Phosphonium-based ionic liquids analogues and their physical properties. *J. Chem. Eng. Data.* **55**, 4632–4637 (2010).
-
50. Mjalli, F. S., Naser, J., Jibril, B., Alizadeh, V. & Gano, Z. Tetrabutylammonium chloride based ionic liquid analogues and their physical properties. *J. Chem. Eng. Data.* **59**, 2242–2251 (2014).
-
51. Su, H.-Z., Yin, J. M., Liu, Q. S. & Li, C. P. Properties of four deep eutectic solvents: density, electrical conductivity, dynamic viscosity and refractive index. *Acta Phys. Chim. Sin.* **31**, 1468–1473 (2015).
-
52. Rodriguez, N. R., Requejo, P. F. & Kroon, M. C. Aliphatic–aromatic separation using deep eutectic solvents as extracting agents. *Ind. Eng. Chem. Res.* **54**, 11404–11412

53. Cardellini, F. *et al.* Novel zwitterionic deep eutectic solvents from trimethylglycine and carboxylic acids: characterization of their properties and their toxicity. *RSC Adv.* **4**, 55990–56002 (2014).

54. Rackett, H. G. Equation of state for saturated liquids. *J. Chem. Eng. Data.* **15**, 514–517 (1970).

55. Shahbaz, K., Mjalli, F. S., Hashim, M. A. & AlNashef, I. M. Prediction of deep eutectic solvents densities at different temperatures. *Thermochim. Acta.* **515**, 67–72 (2011).

56. Spencer, C. F. & Danner, R. P. Improved equation for prediction of saturated liquid density. *J. Chem. Eng. Data.* **17**, 236–241 (1972).

57. Mjalli, F. S., Shahbaz, K. & AlNashef, I. M. Modified Rackett equation for modelling the molar volume of deep eutectic solvents. *Thermochim. Acta.* **614**, 185–190 (2015).

58. Li, B., Feng, Y., Xiong, Z., Yang, W. & Liu, G. Research on AI security enhanced encryption algorithm of autonomous IoT systems. *Inf. Sci. (NY)* **575**, 379–398 (2021).

59. He, Y., Dai, L. & Zhang, H. Multi-branch deep residual learning for clustering and beamforming in user-centric network. *IEEE Commun. Lett.* **24**, 2221–2225 (2020).

60. Meng, F., Cheng, W. & Wang, J. Semi-supervised software defect prediction model based on tri-training. *KSII Trans. Internet Inf. Syst.* **15**, 4028–4042 (2021).

62. Liu, F., Zhang, G. & Lu, J. Heterogeneous domain adaptation: An unsupervised approach. *IEEE Trans. Neural Netw. Learn. Syst.* **31**, 5588–5602 (2020).
63. Ma, Z., Zheng, W., Chen, X. & Yin, L. Joint embedding VQA model based on dynamic word vector. *PeerJ Comput. Sci.* **7**, e353 (2021).
64. Nabavi, M., Nazarpour, V., Alibak, A. H., Bagherzadeh, A. & Alizadeh, S. M. Smart tracking of the influence of alumina nanoparticles on the thermal coefficient of nanosuspensions: application of LS-SVM methodology. *Appl. Nanosci.* **11**, 2113–2128 (2021).
65. Esmaeili-Faraj, S. H. *et al.* Design a neuro-based computing paradigm for simulating of industrial olefin plants. *Chem. Eng. Technol.* **44**, 1382–1389 (2021).
66. Mousavi, N. S., Romero-Martínez, A. & Ramírez-Verduzco, L. F. Predicting the surface tension of mixtures of fatty acid ethyl esters and biodiesel fuels using UNIFAC activity coefficients. *Fluid Phase Equilib.* **507**, 112430 (2020).
67. Moghimihanjani, M. & Vaferi, B. A combined wavelet transform and recurrent neural networks scheme for identification of hydrocarbon reservoir systems from well testing signals. *ASME J. Energy Resour. Technol. Energy Resour. Technol. Energy Resour. Technol.* **143**, 13001 (2021).
68. Jafari Gukeh, M., Moitra, S., Ibrahim, A. N., Derrible, S. & Megaridis, C. M. Machine learning prediction of TiO₂-coating wettability tuned via UV exposure. *ACS Appl. Mater. Interf.* **13**, 46171–46179 (2021).

-
70. Khalifeh, A. & Vaferi, B. Intelligent assessment of effect of aggregation on thermal conductivity of nanofluids-Comparison by experimental data and empirical correlations. *Thermochim. Acta.* **681**, 178377 (2019).
-
71. Liu, Z. *et al.* Investigating pose representations and motion contexts modeling for 3D motion prediction. In: IEEE Transactions on Pattern Analysis and Machine Intelligence, IEEE. <https://doi.org/10.1109/TPAMI.2021.3139918> (2020).
-
72. Vaferi, B., Eslamloueyan, R. & Ayatollahi, S. Application of recurrent networks to classification of oil reservoir models in well-testing analysis. *Energy Sour. A Recover. Util. Environ. Eff.* **37**, 174–180 (2015).
-
73. Shang, K. *et al.* Haze prediction model using deep recurrent neural network. *Atmosphere (Basel)*. **12**, 1625 (2021).
-
74. Rooki, R. Application of general regression neural network (GRNN) for indirect measuring pressure loss of Herschel-Bulkley drilling fluids in oil drilling. *Measurement* **85**, 184–191 (2016).
-
75. Hagan, M.T., Demuth, H.B., & Beale, M. Neural network design. PWS Publishing Co., 1997.
-
76. Mousavi, N. S., Vaferi, B. & Romero-Martínez, A. Prediction of surface tension of various aqueous amine solutions using the UNIFAC model and artificial neural networks. *Ind. Eng. Chem. Res.* **60**, 10354–10364 (2021).
-
77. Wang, Y., Zou, R., Liu, F., Zhang, L. & Liu, Q. A review of wind speed and wind

78. Dizadji, M.R., Yousefi-Koma, A., & Gharehnazifam, Z. 3-Axis attitude control of satellite using adaptive direct fuzzy controller. In: Proceedings of the 2018 6th RSI International Conferences on Robotics Mechatronics, IEEE, 2018: pp. 1–5.

79. Dizaji, M.R., Yazdi, M.R.H., Shirzi, M.A., & Gharehnazifam, Z., Fuzzy supervisory assisted impedance control to reduce collision impact. In: Proceedings of the 2014 Second RSI/ISM International Conference on Robotics Mechatronics, IEEE, 2014: pp. 858–863.

80. Zamani, H. A., Rafiee-Taghanaki, S., Karimi, M., Arabloo, M. & Dadashi, A. Implementing ANFIS for prediction of reservoir oil solution gas-oil ratio. *J. Nat. Gas Sci. Eng.* **25**, 325–334 (2015).

81. Motahari-Nezhad, M. & Jafari, S. M. ANFIS system for prognosis of dynamometer high-speed ball bearing based on frequency domain acoustic emission signals. *Measurement* **166**, 108154 (2020).

82. Shojaei, M.-J., Bahrami, E., Barati, P. & Riahi, S. Adaptive neuro-fuzzy approach for reservoir oil bubble point pressure estimation. *J. Nat. Gas Sci. Eng.* **20**, 214–220 (2014).

83. Cao, Y., Kamrani, E., Mirzaei, S., Khandakar, A. & Vaferi, B. Electrical efficiency of the photovoltaic/thermal collectors cooled by nanofluids: machine learning simulation and optimization by evolutionary algorithm. *Energy Rep.* **8**, 24–36 (2022).

84. Seyed Alizadeh, S. M. *et al.* Retrograde gas condensate reservoirs: reliable estimation of dew point pressure by the hybrid neuro-fuzzy connectionist

85. Daryayehsalameh, B., Nabavi, M. & Vaferi, B. Modeling of CO₂ capture ability of [Bmim][BF₄] ionic liquid using connectionist smart paradigms. *Environ. Technol. Innov.* **22**, 101484 (2021).

86. Karimi, M., Alibak, A. H., Alizadeh, S. M. S., Sharif, M. & Vaferi, B. Intelligent modeling for considering the effect of bio-source type and appearance shape on the biomass heat capacity. *Measurement* **189**, 110529 (2021).

87. Rehamnia, I., Benlaoukli, B., Jamei, M., Karbasi, M. & Malik, A. Simulation of seepage flow through embankment dam by using a novel extended Kalman filter based neural network paradigm: case study of Fontaine Gazelles Dam. *Algeria. Measurement.* **176**, 109219 (2021).

88. Jiang, Y., Zhang, G., Wang, J. & Vaferi, B. Hydrogen solubility in aromatic/cyclic compounds: Prediction by different machine learning techniques. *Int. J. Hydrogen Energy.* **46**, 23591–23602 (2021).

89. Nabipour, N., Qasem, S. N., Salwana, E. & Baghban, A. Evolving LSSVM and ELM models to predict solubility of non-hydrocarbon gases in aqueous electrolyte systems. *Measurement* **164**, 107999 (2020).

90. Xie, J., Liu, X., Lao, X. & Vaferi, B. Hydrogen solubility in furfural and furfuryl bio-alcohol: Comparison between the reliability of intelligent and thermodynamic models. *Int. J. Hydrogen Energy.* **73**, 36056–36068 (2021).

91. Vaferi, B., Eslamloueyan, R. & Ghaffarian, N. Hydrocarbon reservoir model detection from pressure transient data using coupled artificial neural network-Wavelet transform approach. *Appl. Soft Comput. J.* **47**, 63–75 (2016).

- functionalized bed from its design and operating parameters. *Ind. Eng. Chem. Res.* **57**, 259–267 (2018).
-
93. Ghanbari, S. & Vaferi, B. Experimental and theoretical investigation of water removal from DMAZ liquid fuel by an adsorption process. *Acta Astronaut.* **112**, 19–28 (2015).
-
94. Zhou, Z., Davoudi, E. & Vaferi, B. Monitoring the effect of surface functionalization on the CO₂ capture by graphene oxide/methyl diethanolamine nanofluids. *J. Environ. Chem. Eng.* **9**, 106202 (2021).
-
95. Moosavi, S. R., Vaferi, B. & Wood, D. A. Auto-characterization of naturally fractured reservoirs drilled by horizontal well using multi-output least squares support vector regression. *Arab. J. Geosci.* **14**, 545 (2021).
-
96. Hosseini, S. & Vaferi, B. Determination of methanol loss due to vaporization in gas hydrate inhibition process using intelligent connectionist paradigms. *Arab. J. Sci. Eng.* <https://doi.org/10.1007/s13369-021-05679-4> (2021).
-
97. Yang, W. *et al.* A privacy-preserving aggregation scheme based on negative survey for vehicle fuel consumption data. *Inf. Sci.* **570**, 526–544. <https://doi.org/10.1016/j.ins.2021.05.009> (2020).
-
98. Nowosielski, B., Jamrógiewicz, M., Łuczak, J., Śmiechowski, M. & Warmińska, D. Experimental and predicted physicochemical properties of monopropylamine-based deep eutectic solvents. *J. Mol. Liq.* **309**, 113110 (2020).
-

Download PDF

School of Mechanical Engineering, Center of Excellence in Energy Conversion (CEEC), Sharif University of Technology, Azadi Avenue, P. O. Box 11365-9567, Tehran, Iran
Mohammadjavad Abdollahzadeh

Department of Civil and Environmental Engineering, College of Engineering, Villanova University, Pennsylvania, USA
Marzieh Khosravi

Computer Engineering Department, Tehran North Branch, Islamic Azad University, Tehran, Iran
Behnam Hajipour Khire Masjidi

Department of Mechanical Engineering, Behbahan Khatam Alanbia University of Technology, Behbahan, Iran
Amin Samimi Behbahan

Department of Mechanical Engineering and Mechanics, Drexel University, Philadelphia, PA, 19104, USA
Ali Bagherzadeh

Department of Transportation Engineering, Karadeniz Technical University, Trabzon, 61080, Turkey
Amir Shahkar

Department of Electrical Engineering, Garmsar Branch, Islamic Azad University, Semnan, Iran
Farzad Tat Shahdost

Contributions

All authors have equally engaged in this research article.

Corresponding author

Correspondence to [Farzad Tat Shahdost](#).

Ethics declarations

Competing interests

The authors declare no competing interests.

Additional information

Publisher's note

Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Rights and permissions

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

Reprints and Permissions

About this article

Cite this article

Abdollahzadeh, M., Khosravi, M., Hajipour Khire Masjidi, B. *et al.* Estimating the density of deep eutectic solvents applying supervised machine learning techniques. *Sci Rep* **12**, 4954 (2022). <https://doi.org/10.1038/s41598-022-08842-5>

Received

30 January 2022

Accepted

15 March 2022

Published

23 March 2022

DOI

<https://doi.org/10.1038/s41598-022-08842-5>

Share this article

Anyone you share the following link with will be able to read this content:

Download PDF

Subjects [Chemical engineering](#) • [Materials chemistry](#)

Scientific Reports (*Sci Rep*) | ISSN 2045-2322 (online)

© 2022 Springer Nature Limited