


# Run-Time Storage Organization



# Procedure Activations

- Each execution of a procedure is called as its *activation*.
- *Lifetime* of an activation of a procedure is the sequence of the steps between the first and the last steps in the execution of that procedure (including the other procedures called by that procedure).
- If a and b are procedure activations, then their lifetimes are either non-overlapping or are nested.
- If a procedure is recursive, a new activation can begin before an earlier activation of the same procedure has ended.

# Activation Records



- Information needed by a single execution of a procedure is managed using a contiguous block of storage called **activation record**.
- An activation record is allocated when a procedure is entered, and it is de-allocated when that procedure exited.
- Size of each activation record can be determined at compile time (Although the actual location of the an activation record determined at run-time).
  - Even though the procedure has a local variable and its size depends on a parameter, its size is determined at the run time.

# Activation Records (cont.)

return value	← The returned value of the called procedure is returned in this field to the calling procedure. In practice, we may use a machine register for the return value.
actual parameters	← The field for actual parameters is used by the calling procedure to supply parameters to the called procedure.
optional control link	← The optional control link points to the activation record of the caller.
optional access link	← The optional access link is used to refer to nonlocal data held in other activation records.
saved machine status	← The field for saved machine status holds information about the state of the machine before the procedure is called.
local data	← The field of local data holds data that local to an execution of a procedure..
temporaries	← Temporary variables is stored in the field of temporaries.

# Activation Records (Ex1)

```
program main;  
  procedure p;  
    var a:real;  
    procedure q;  
      var b:integer;  
      ...  
    end q;  
    ... q;  
  end p;  
  procedure s;  
    var c:integer;  
    ...  
  end s;  
  ... p; s;  
end main;
```



# Activation Records for Recursive Procedures


```
program main;  
  procedure p;  
    function q(a:integer):integer;  
      begin  
        if (a=1) then q:=1;  
        else q:=a+q(a-1);  
      end q;  
    begin q(3); end p;  
begin p; end main;
```

main	
p	
a: 3	q(3)
a:2	q(2)
a:1	q(1)

# Creation of An Activation Record


- Who allocates an activation record of a procedure?
  - Some part of the activation record of a procedure is created by that procedure immediately after that procedure is entered.
  - Some part is created by the caller of that procedure before that procedure is entered.
- Who deallocates?
  - Callee de-allocates the part allocated by Callee.
  - Caller de-allocates the part allocated by Caller.

# Creation of An Activation Record (cont.)





# Variable Length Data



Variable length data is allocated after temporaries, and there is a link to from local data to that array.

# Access to Nonlocal Names

- Scope rules of a language determine the treatment of references to nonlocal names.
- Scope Rules:
  - **Lexical Scope (Static Scope)**
    - Determines the declaration that applies to a name by examining the program text alone at compile-time.
    - Most-closely nested rule is used.
    - Pascal, C, ..
  - **Dynamic Scope**
    - Determines the declaration that applies to a name at run-time.
    - Lisp, APL, ...

# Non Local Names


---

- A procedure may access to a nonlocal name using:
  - access links in activation records, or
  - displays (an efficient way to access to nonlocal names)

# Access Links

```
program main;  
  var a:int;  
  procedure p;  
    var d:int;  
    a:=1;  
  end p;  
  procedure q(i:int);  
    var b:int;  
    procedure s;  
      var c:int;  
      call p;  
    end s;  
    if (i<>0) then q(i-1)  
    else s;  
  end q;  
  q(1);  
end main;
```

Access  
Links



# Displays

---

- An array of pointers to activation records can be used to access activation records.
- This array is called as displays.
- For each level, there will be an array entry.

1:
2:
3:


Current activation record at level 1

Current activation record at level 2

Current activation record at level 3

# Accessing Nonlocal Variables

```
program main;  
  var a:int;  
  procedure p;  
    var b:int;  
    call q;  
  procedure q();  
    var c:int;  
    c:=a+b;  
  end q;  
end p;  
call p;  
end main;
```



# Accessing Nonlocal Variables using Display

```
program main;  
  var a:int;  
  procedure p;  
    var b:int;  
    call q;  
  procedure q();  
    var c:int;  
    c:=a+b;  
  end q;  
end p;  
call p;  
end main;
```

