

Description	unit	CB-FWc/115T/Sw	CB-FWc/135T/Sw	CB-FWc/160T/Sw	CB-FWc/175T/Sw	CB-FWc/225T/Sw	CB-FWc/270T/Sw	CB-FWc/315T/Sw	CB-FWc/345T/Sw	CB-FWc/400T/Sw	معرفی
Nominal cooling capacity	Kw(TR)	404.3(115)	474.7 (135)	562.6(160)	615.3(175)	791.1(225)	949.3(270)	1107.5(315)	1213(345)	1406.4(400)	ظرفیت سرمایشی اسمی
Dimensions(L*W*H)	mm	2700×800×2000	2935×900×2100	2979×900×2400	2958×1350×2400	3100×1350×2300	3400×1848×2300	3400×1848×2300	3400×1848×2450	3400×1848×3000	ابعاد
Operating Weight/unit(approx)	Kg	2750	3025	3750	4000	5040	6250	7280	7500	8300	
Compressor type	-	Semi-hermetic screw									مدل کمپرسور
Model	-	BSC – 110W	BSC – 130W	BSC – 155W	BSC – 170W	BSC – 220W	BSC – 110W	BSC – 155W	BSC – 170W	BSC – 170W BSC – 220W	مدل
Quantity	No.	1	1	1	1	1	2	2	2	2	تعداد
Power supply	v/ph/Hz	-	-	400+10%/3/50	-	-	-	-	-	-	منبع تغذیه
Cooler (Dx-Shell & tube type)	-	-	-	-	-	-	-	-	-	-	
Quantity	No.	1	1	1	1	1	2	2	2	2	تعداد
Water flow rate max	USGPM	330	400	465	510	670	795	930	1020	1175	حداکثر جریان فشار آب
Water connection size(Nb)	Inches	6	6	6	8	8	6.6	6.6	8.8	8.8	اتصال آب
Condenser(shell & tube type)	-	-	-	-	-	-	-	-	-	-	کندانسور (پوشته و نوع لوله)
Quantity	No.	1	1	1	1	1	2	2	2	2	تعداد
Water flow rate max	USGPM	535	640	750	825	1075	1285	1500	1645	1900	حداکثر جریان فشار آب
Condenser connection	Inches	4	4	4	5	6	4.4	4.4	5.5	5.6	اتصال کندانسور