







MOBILE :+989387050531







TEL : +98(21)88698971









IRAN-TEJARAT.COM









EMAIL: info@iran-tejarat.com









۱۳۹۶/۰۸/۱۴

مدل ردیف	مشخصات فنی	HDCVI	تصویر	قیمت (ریال)
1 DH-HAC-HFW2401EP	1/3" 4.1Megapixel CMOS 25fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD dual-output OSD Menu Max. IR length 40m, Smart IR IP67, DC12V			3,770,000
2 DH-HAC-HFW2401DP	1/3" 4.1Megapixel CMOS 25fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD dual-output OSD Menu Max. IR length 80m, Smart IR IP67, DC12V			4,030,000
3 DH-HAC-HFW1400RP-VF-IRE6	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm vari-focal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V			4,550,000
4 DH-HAC-HFW1400DP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V			3,120,000
5 DH-HAC-HFW1400SP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V			2,730,000
6 DH-HAC-HFW1400TP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V			2,470,000
7 DH-HAC-HFW2231RP-Z-IRE6	1/2.8" 2.1Megapixel CMOS, (Starlight) 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Motorized lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V			6,110,000








8	DH-HAC-HFW2231EP	<p>1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 40m, Smart IR IP67, DC12V</p>		3,770,000
9	DH-HAC-HFW2231DP	<p>1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V</p>		4,100,000
10	DH-HAC-HFW2221RP-Z-IRE6-0722	<p>1/2.7" 2.1Megapixel CMOS 25/30fps@1080P,25/30/50/60fps@720P HD and SD dual-output OSD Menu, control over coaxial cable WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, 3DNR 7~22mm motorized lens Max. IR LEDs length 60m, Smart IR IP67, DC12V</p>		Call
11	DH-HAC-HFW2220RP-Z-IRE6	<p>1/2.8" 2.4Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P HD and standard definition switchable OSD Menu, control over coaxial cable DWDR, Day/Night(ICR), AWB, AGC, BLC, 3D-DNR 2.7~12mm motorized lens Max. IR LEDs length 60m, Smart IR IP67, DC12V</p>		5,330,000
12	DH-HAC-HFW2221DP-0360B	<p>1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P HD and SD dual-output OSD Menu, control over coaxial cable WDR(120dB), Day/Night(ICR),AWB, AGC, BLC, 3DNR 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR IP67, DC12V</p>		Call
13	DH-HAC-HFW1220RP-VF-IRE6	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 60m, Smart IR IP67, DC12V</p>		3,510,000
14	DH-HAC-HFW1220DP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR IP67, DC12V</p>		2,430,000






15	DH-HAC-HFW1220BP-B-0360B	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		2,280,000
16	DH-HAC-HFW1220SP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,950,000
17	DH-HAC-HFW1200BP-B-0360B	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		2,080,000
18	DH-HAC-HFW1200SP-0360B	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		1,780,000
19	DH-HAC-HFW1200SLP NEW Product	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		1,500,000
20	DH-HAC-HFW1200RMP-0360B Metal Case	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V</p>		1,560,000
21	DH-HAC-HUM1220AP	<p>2MP HDCVI MotionEye Camera 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR , Support OSD Menu 12m/100°detecting range/angle Two level(jumper) detection sensitivity adjustable Built-in tamper switch DC12V</p>		2,680,000
22	DH-HAC-HUM3201B NEW Product	<p>1/2.8" 2Megapixel CMOS(Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens HD and SD output switchable WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR , Support OSD Menu DC12V</p>		3,380,000

23	DH-HAC-HFW1100RP-VF	<p>1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.7~12mm vari-focal lens Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		2,080,000
24	DH-HAC-HFW1100SP	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,340,000
25	DH-HAC-HFW1100SL	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,110,000
26	DH-HAC-HFW1100RMP-0280B Metal Case	<p>1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.8mm fixed lens Max. IR LEDs length 20m, Smart IR IP67, DC12V</p>		1,150,000
27	DH-HAC-HFW1100RMP-0360B Metal Case	<p>1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens Max. IR LEDs length 20m, Smart IR IP67, DC12V</p>		1,150,000
28	DH-HAC-HFW1100RP	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V</p>		1,010,000
29	DH-HAC-HDW2401EMP	<p>1/3" 4.1Megapixel CMOS 25fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD dual-output OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>		3,640,000
30	DH-HAC-HDW1400EMP	<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>		2,730,000








31	DH-HAC-HDW1400MP	<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		2,470,000
32	DH-HAC-HDBW2231FP	<p>1/2.8" 2.1Megapixel CMOS(Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, IK10, DC12V</p>		3,900,000
33	DH-HAC-HDW2231EMP	<p>1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67,DC12V</p>		3,770,000
34	DH-HAC-HDBW2221RP-Z	<p>1/2.7" 2.1Megapixel CMOS 25/30fps@1080P,25/30/50/60fps@720P HD and SD dual-output OSD Menu, control over coaxial cable WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, 3DNR 2.7~12mm motorized lens Max. IR LEDs length 30m, Smart IR IP67, IK10, DC12V</p>		5,660,000
35	DH-HAC-HDBW2220RP-Z	<p>1/2.8" 2.4Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P HD and standard definition switchable OSD Menu, control over coaxial cable DWDR, Day/Night(ICR), AWB, AGC, BLC, 3D-DNR 2.7~12mm motorized lens Max. IR LEDs length 30m, Smart IR IP67, IK10, DC12V</p>		5,150,000
36	DH-HAC-HDBW1220RP-VF	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, IK10, DC12V</p>		3,250,000
37	DH-HAC-HDW1220EMP-A	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens Built-in Mic HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		2,050,000
38	DH-HAC-HDW1220EMP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		1,910,000
















39	DH-HAC-HDW1220MP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,820,000
40	DH-HAC-HDW1200MP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		1,560,000
41	DH-HAC-HDW1200EMP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P HD and SD output switchable 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		1,780,000
42	DH-HAC-HDW1200EMP-A Metal Case	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P Built-in MIC Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens (6mm optional) Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		1,920,000
43	DH-HAC-HDW1100MP-0360B	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,040,000
44	DH-HAC -HDW1100RP-0360B	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V</p>		1,010,000
45	SD22204I-GC	<p>Powerful 4x optical zoom (2.7mm~11mm) Max. 25/30fps@1080P, 50/60fps@720P resolution WDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC Max 100°/s pan speed HD & SD Switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern IP66, IK10, OSD</p>		6,370,000

46	DH-SD59225I-HC-S2	<p>1/2.8" 2Megapixel Exmor R CMOS (Starlight) Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution 4.8mm ~ 120mm 25x optical zoom WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Control over coaxial cable 1-channel BNC HDCVI/CVBS output (switchable) Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 Alarm in/out 1 Audio Input , RS485 IR Distance up to 150m IP66,OSD</p>		30,550,000
47	SD59230I-HC	<p>2MP 30x Starlight IR PTZ HDCVI Camera 1/2.8" Exmor R CMOS Max. 25/30fps @1080P(1920x1080) & 20/30/50/60fps @720Presolution 4.5mm~135mm 30x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Audio(in/out) 1 / 1 Built-in 2/1 Alarm in/out IR Distance up to 150m IP66,OSD</p>		39,000,000
48	DH-HCVR5104HS-S3	<p>4CH 720P/1080N real Time , 1080P Non-real Time CVI Recorder H.264 dual-stream video compression 4CH Playback Tribrid (IP+CVI+Analogue) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output RS485 , PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		4,100,000
49	DHI-XVR5104HS	<p>4CH Penta-brid 1080P Non-real Time , 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		4,100,000
50	DH-HCVR7104H-4M	<p>4CH 4Mp None-real time, 1080P Real-Time CVI Recorder H.264+/H.264 Dual-stream video compression Tribrid(IP+CVI+Analogue) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] 1/4/6 Display 1/4 CH Playback 1 Audio Input/ 1 Audio Output 1 SATA Port , Up to 6 TB 1 HDMI(4K),1 VGA simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 1 LAN Interface(1000M) DC12V/2A Power Supply P2P Support</p>		7,150,000

51	DH-HCVR5108HS-S3	<p>8CH 720P/1080N real Time , 1080P Non-real Time CVI Recorder H.264 dual-stream video compression 8CH Playback Tribrid (IP+CVI+Analogue) N+M [8+ 4 IP up to 5 Megapixel(48 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output RS485 , PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>	6,890,000	
52	DHI-XVR5108HS	<p>8CH Penta-brid 1080P Non-real Time , 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 5 Megapixel(48 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>	6,890,000	
53	DH-HCVR7108H-4M	<p>8CH 4Mp None-real time, 1080P Real-Time CVI Recorder H.264+/H.264 Dual-stream video compression Tribrid(IP+CVI+Analogue) N+M [8+4 IP up to 5 Megapixel(48 Mbps)] 1/4/8/9/16 Display 1/4/9CH Playback 1 Audio Input/ 1 Audio Output 1 SATA Port , Up to 6 TB 1 HDMI(4K),1 VGA simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 1 LAN Interface(1000M) DC12V/2A Power Supply P2P Support</p>	10,270,000	
54	DH-HCVR7208AN-4M	<p>8CH 4Mp None-real time, 1080P Real-Time CVI Recorder H.264+/H.264 Dual-stream video compression Tribrid(IP+CVI+Analogue) N+M [8+4 IP up to 5 Megapixel(48 Mbps)] 1/4/8/9/16 Display 1/4/9CH Playback 1 Audio Input/ 1 Audio Output 2 SATA Port , Up to 12 TB 1 HDMI(4K),1 VGA simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 1 LAN Interface(1000M) DC12V/4A Power Supply P2P Support</p>	13,520,000	
55	DH-HCVR5216A-S3	<p>16CH 720P/1080N real Time , 1080P Non-real Time CVI Recorder H.264 dual stream video compression 16 CH Playback Tribrid (IP+CVI+Analogue) N+M [16+8 IP up to 5 Megapixel(96 Mbps)] 4 Audio Input , 1 Audio Output 16*Alarm Input , 3*Relay Output 2 SATA Port , Up to 12 TB HDMI , VGA simultaneous video Output RS485 , PTZ Support 1*USB 2.0 + 1*USB 30. 10/100/1000 Mbps LAN Interface P2P Support</p>	14,170,000	

56 DH-HCVR5216AN-S3	<p>16CH 1080P Non-real Time , 1080N/720P real-Time CVI Recorder H.264+/H.264 dual stream video compression 16 CH Playback Tribrid (IP+CVI+Analogue) N+M [16+8 IP up to 5 Megapixel(96 Mbps)] 1 Audio Input , 1 Audio Output 2 SATA Port , Up to 12 TB HDMI , VGA simultaneous video Output Support Smart Search and Intelligent Video System RS485 for PTZ Support 1*USB 2.0 + 1*USB 3.0. 10/100/1000 Mbps LAN Interface P2P Support</p>	12,480,000		
57 DHI-XVR5216A	<p>16CH Penta-brid 1080P Non-real Time , 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96 Mbps)] 4 Audio Input / 1 Audio Output 16 Alarm Input / 3 Relay output 2 SATA Port , Up to 12 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface P2P Support</p>	14,170,000		
58 DH-HCVR7216AN-4M	<p>16CH 4Mp None-real time, 1080P Real-Time CVI Recorder H.264+/H.264 Dual-stream video compression Tribrid(IP+CVI+Analogue) N+M [16+8 IP up to 5 Megapixel(96 Mbps)] 1/4/8/9/16/25 Display 1/4/9/16CH Playback 1 Audio Input/ 1 Audio Output 2 SATA Port , Up to 12 TB 1 HDMI(4K),1 VGA simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 1 LAN Interface(1000M) DC12V/5A Power Supply P2P Support</p>	18,720,000		
59 DH-XVR5416L		<p>16CH Penta-brid 1080N/720P Real-Time,1080P None-Real time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 6 TB 1 e-SATA 2*HDMI , VGA , TV simultaneous video Output RS485 , RS 232 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface P2P Support</p>	25,740,000	
60 DH-XVR7416L		<p>16CH Penta-brid 1080P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 6 TB 1 e-SATA 2*HDMI , VGA , TV simultaneous video Output RS485 , RS 232 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface P2P Support</p>	35,100,000	

61 DH-HCVR8816S-S3	<p>All channel 1080P realtime recording Support HDCVI/AHD/Analog/IP Video input H.264 dual-stream video compression 16 channel synchronous realtime playback Tribrid (IP+CVI+Analogue)N+M[16+48 up to 12Megapixel(384Mbps)] 16 Audio Input , 1 Audio Output 16*Alarm Input , 6*Relay Output 8 SATA ports, up to 64TB, 1 eSATA HDMI 1/VGA simultaneous video output,HDMI2/VGA(HDMI1) independent video output RS485 , PTZ Support 4 ports (2 Rear USB3.0, 2 Front USB2.0) 2*10/100/1000 Mbps LAN Interface IVS: Tripwire, Intrusion, Abandoned/Missing, Scene Change, Face Detection, People Counting, Smart Tracking P2P Support</p>		Call
62 DHI-HCVR4232AN-S3	<p>32 CH 720P/1080N Non-real Time CVI Recorder H.264 dual-stream video compression 16CH Playback Tribrid(IP+CVI+Analogue)[16CH IP up to 5 Megapixel(64 Mbps)] 1 Audio Input/ 1 Audio Output 2 SATA Port , Up to 12 TB HDMI , VGA , simultanous video Output RS485 for PTZ support 2*USB(1 Rear USB3.0, 1 Front USB2.0) 10/100/1000 Mbps LAN Interface P2P Support</p>		14,950,000
63 DH-XVR4232AN	<p>32 Channel Penta-brid 1080N None-Real time H.264 video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[16 IP up to 5 Megapixel(64Mbps)] 1 Audio IN / 1 Audio Out 2 SATA Port , Up to 16 TB 1 HDMI, 1 VGA, 1 TV RS485 1 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface P2P Support</p>		14,950,000
64 DH-HCVR5232AN-S3	<p>32 Channel Tribrid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 video compression 1/4/9/16CH Playback Tribrid (IP+CVI+Analogue)[16 up to 5Megapixel(64Mbps)] 1 Audio IN / 1 Audio Out 2 SATA Port , Up to 16 TB 1 HDMI, 1 VGA, 1 TV RS485 1 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface P2P Support</p>		22,230,000
65 DH-XVR5232AN	<p>32 Channel Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 1 Audio IN / 1 Audio Out 2 SATA Port , Up to 16 TB 1 HDMI, 1 VGA, 1 TV RS485 1 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface P2P Support</p>		22,230,000

66	DH-XVR5432L		<p>32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 8 TB 1 e-SATA Port 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface Smart Search and Intelligent Video System P2P Support</p>		41,600,000
67	DH-XVR5832S		<p>32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 16 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 8 SATA Port , Up to 8 TB 1 e-SATA Port 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422 2 USB 3.0, 2 USB 2.0 10/100/1000 Mbps LAN Interface Smart Search and Intelligent Video System P2P Support</p>		50,700,000
68	PFT2100		<p>HDMI-HDCVI Converter *Input HDMI video signal, self-adaptive output HDCVI signal *HDMI support mode, 1024*768@60Hz, 1280*720@50/60Hz, 1280*1024@60Hz,1600*1200@60Hz, 1920*1080@50/60Hz *HDCVI output format, 720P/50, 720P/60, 1080P/25, 1080P/30 *Output Cable Length 1080P: 75-5 coaxial cable support 300m/720P: 75-5 coaxial cable support 500m *Power:DC12V</p>		3,580,000
69	TP2105		<p>HDCVI Video Converter real time non-compression transmission *Input: 1*HDCVI (BNC) *Output: 1*HDCVI (BNC), 1*CVBS (BNC), 1*HDMI, 1*VGA *1080p/720p: 75-5 coaxial support 100m Input Transmission Distance *1080p/720p: 75-5 coaxial support 100m HDCVI Output Transmission Distance *Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s *RS485</p>		3,770,000
70	PFM801		<p>*1 Channel HDCVI Transmission Signal *720P, 400M(max); 1080P, 200M(max)Transmission Distance *Input voltage DC24-36V, can provide DC12V8W(max) power supply to remote cameras *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal and 1-ch DC power *Excellent anti-thunder, anti-static and anti-interference capabilities *Compatible with HDCVI/TVI/AHD format</p>		510,000
71	PFM900		<p>4" IPS screen and QWERTY flip keyboard with 45keys Support IP configuration via Onvif protocol Support HDCVI/ Analog self-adaptive access Support 8x digital zoom Support audio and RS485 control TDR cable detection and network connection test Video screen shot, video recording and playback Support POE/ DC12V longer power supply Dual LED flashlight</p>		26,650,000